## <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

### 1. Identification of the substance / mixture and of the company / undertaking

1.1 Product Indentifier:

Product Identity:

#### Alternate Names:

## <u>Flush</u>

Specialty Embalming Chemical

Specialty Embalming Chemical

See Technical Data Sheet

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Intended Use:

Application Method:

1.3 Details Of The Supplier Of the Safety Daty Sheet:

Company Name:

Emergency: CHEMTREC (USA)

Arlington Chemical Co. (Customer Service)

Arlington Chemical Co. 2913 "51<sup>st</sup>" Place Tuxedo, MD 20785

800-424-9300

301-772-6150

### 2. Hazard Identification Of The Product

#### 2.1 Classification Of The Substance or Mixture:

Flam. Liq: 3;H226	Flammable liquid and vapor
Acute Tox: 4;H302	Harmful if swallowed
Acute Tox: 3;H311	Toxic in contact with skin
Acute Tox: 2;H330	Fatal if inhaled
Skin Corr: 1B;H314	Causes severe skin burns and eye damage
Eye Dam: 1;H318	Causes serious eye damage
Skin Sens: 1;H317	May cause an allergic skin reaction
Mutations: 2;H341	Suspected of causing genetic defects
Carc.: 1B;H350	May cause cancer
STOT SE 2:H371	May cause damage to organs
Aquatic Chronic: 1;H410	Very toxic to aquatic life with long lasting effects

# <u>Flush</u>

## ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

#### 2.2. Label Elements:

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows:



11000	Elemente ble lieu id en daar en
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes Severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H330	Fatal if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H371b	May cause damage to organs if inhaled or swallowed
H371h	May cause damage to organs in contact with skin
H440	Very toxic to aquatic life with long-lasting effects

## (PREVENTION):

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat / sparks / open flames / hot surfaces - NO SMOKING
P241	Use explosion-proof electrical / ventilation / light / equipment
P261	Avoid breathing dust / fume / gas / mist / vapors / spray
P264	Wash thoroughly after handling
P270	Do not eat, drink or smoke when using this product.
P271	Use in a well-ventilated area; or use only outdoors
P272	Contaminated work clothing should not be allowed out of the workplace
P273	Avoid release to the environment
P280	Wear protective gloves / eye protection / face protection
P284	Wear respiratory protection

# <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

P301 + 330 + 331	IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.		
P302 + 352	IF ON SKIN: Wash with plenty of soap and water		
P303 + 361 + 353 IF ON SKIN (or hair): Remove / Take of immediately all contaminated clothing skin with water / shower			
P304 + 312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell			
P305 + 351 + 338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact if present and easy to do - continue rinsing			
P308 + 313	IF exposed or concerned: Get medical advice / attention		
P309 + 311	If exposed or you feel unwell Call a POISON CENTER or doctor / physician		
P310	Immediately call a POISON CENTER or doctor / physician		
P320	Special treatment is urgent (see information on this label)		
P333 + 313	If skin irritation or a rash occurs: Get medical advice / attention		
P340	Remove victim to fresh air and keep at rest in a position comfortable for breathing		
P363	Wash contaminated clothing before reuse		
P370 + 378	+ 378 In case of fire: Use alcohol resistant foam, CO2, powder, water spray for extinction. In our use water jet		
P391	Collect spillage		
(STORAGE):			
P402 + 233	Store in a well ventilated place. Keep container tightly closed		
P302 + 352	IF ON SKIN: Wash with plenty of soap and water		
(DISPOSAL):			
P501 Dispose of contents / container in accordance with local / national regulations			

## 3. Composition / Information On Ingredients

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES THAT PRESENT A HAZARD WITHIN THE MEANING OF THE RELEVANT STATE AND FEDERAL HAZARDOUS SUBSTANCES REGULATIONS.

INGREDIENTS / CHEMICAL DESIGNATIONS	WEIGHT %	GHS CLASSIFICATION	Notes
Formaldehyde CAS Number: 000050-00-0	23 - 50	Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 Carc. 1B;H350 Muta. 2;H341 Skin Corr. 1B;H314 Skin Sens. 1;H317	(1) (2)
Methyl Alcohol CAS Number: 000067-56-1	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT SE 1;H370	(1) (2)

# <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

NOTES:

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

THE FULL TEXTS OF THE PHRASES ARE SHOWN IN SECTION 16.

## 4. First Aid Measures

4.1. Description of first aid measures:

	MOVE VICTIM TO FRESH AIR
	CALL 911 OR EMERGENCY MEDICAL SERVICE IF DEEMED NECESSARY
	GIVE ARTIFICIAL RESPIRATION IF VICTIM IS NOT BREATHING
	Do not use "mouth-to-mouth" method if victim ingested or inhaled the
	SUBSTANCE; GIVE ARTIFICIAL RESPIRATION WITH AID OF A POCKET MASK
	EQUIPPED WITH A ONE-WAY VALVE OR THEIR PROPER RESPIRATORY MEDICAL
	DEVICE.
	ADMINISTER OXYGEN IF BREATHING IS DIFFICULT
	REMOVE AND ISOLATE CONTAMINATED CLOTHING AND SHOES
	IN CASE OF CONTACT WITH SUBSTANCE, IMMEDIATELY FLUSH SKIN OR EYES
	WITH RUNNING WATER FOR AT LEAST 20 MINUTES.
	IN CASE OF BURNS, IMMEDIATELY COOL AFFECTED SKIN FOR AS LONG AS
	POSSIBLE WITH COLD WATER. DO NOT REMOVE CLOTHING IF ADHERING TO
	SKIN.
General	KEEP VICTIM WARM AND QUIET
	EFFECTS OF EXPOSURE (INHALATION, INGESTION OR SKIN CONTACT) TO
INHALATION	SUBSTANCE MAY BE DELAYED. ENSURE THAT MEDICAL PERSONNEL ARE AWARE
Eyes, Skin	OF THE MATERIAL(S) INVOLVED AND TAKE PRECAUTIONS TO PROTECT
INGESTION	THEMSELVES.
INCLOTION	MOVE VICTIM(S) TO FRESH AIR. CALL EMERGENCY MEDICAL CARE. APPLY
	ARTIFICIAL RESPIRATION IF VICTIM IS NOT BREATHING. DO NOT USE "MOUTH-TO-
	MOUTH" METHOD IF VICTIM INGESTED OR INHALED THE SUBSTANCE; GIVE
	ARTIFICIAL RESPIRATION WITH AID OF A POCKET MASK EQUIPPED WITH A ONE-
	WAY VALVE OR THEIR PROPER RESPIRATORY MEDICAL DEVICE. ADMINISTER
	OXYGEN IF BREATHING IS DIFFICULT.
	IRRIGATE COPIOUSLY WITH CLEAN FRESH WATER FOR AT LEAST 15 MINUTES,
	HOLDING THE EYELIDS APART AND SEEK MEDICAL ATTENTION.
	REMOVE AND ISOLATE CONTAMINATED CLOTHING AND SHOES. IN CASE OF
	CONTACT WITH SUBSTANCE, IMMEDIATELY FLUSH SKIN OR EYES WITH RUNNING
	WATER FOR AT LEAST 20 MINUTES. SHOWER AND WASH WITH SOAP AND
	WATER. KEEP VICTIM WARM AND QUIET.
	IF ACCIDENTALLY SWALLOWED OBTAIN IMMEDIATE MEDICAL ATTENTION. KEEP
	AT REST. DO NOT INDUCE VOMITING.
	Page 4 of 14

# <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE: 05

05/28/2015

4.2. Most important symptoms and effects, both acute and delayed:

Overview:	Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. Reproductive or genetic defect hazard. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.		
	Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non- allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.		
INHALATION:	Fatal if inhaled. May cause damage to organs		
EYES:	Causes serious eye damage		
SKIN:	Toxic in contact with skin. May cause an allergic skin reaction. Causes severe skin burns and eye damage.		
INGESTION:	Harmful if swallowed		

5. Fire-fighting Measures

# 5.1. Extinguishing Media:

Dry chemical, foam, carbon dioxide and water fog

5.2. Special hazards arising from the substance or mixture:

-	May form formaldehyde gas, carbon oxides, hydrogen, formic acid and various		
	hydrocarbons. Incomplete combustion may also produce irritating smoke and toxic		
	and/or irritating gases or fumes		
-	Obtain special instructions before use		
-	Do not handle until all safety precautions have been read and understood		
-	Keep away from heat / sparks / open flames / hot surfaces – No smoking		
-	Use explosion-proof electrical / ventilating / light / equipment		
-	Avoid breathing dust / fume / gas / mist / vapors / spray		
5.3. Advice For Fire-Fighters:			

-	Wear positive pressure self-contained breathing apparatus (SCBA)		
-	Wear chemical protective clothing that is specifically recommended by the manufacturer.		
	It may provide little or no thermal protection		
-	Structural firefighters' protective clothing provides limited protection in fire situations		
	ONLY; it is not effective in spill situations where direct contact with the substance is		
	possible		
-	Flammable/combustible material		
	Nov be ignited by best sporks or flowes		

- May be ignited by heat, sparks or flames

# <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

5.3. Advice For Fire-Fighters (Con't):

-	Vapors may form explosive mixtures with air
-	Vapors may travel to source of ignition and flash back
-	Most vapors are heavier than air. They will spread along ground and collect in low or
	confined areas (sewers, basements, tanks)
-	Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire
	or explosion hazard
-	Containers may explode when heated
-	Many liquids are lighter than water
-	May cause toxic effects if inhaled or ingested/swallowed
-	Contact with substance may cause severe burns to skin and eyes
-	Fire will produce irritating, corrosive and/or toxic gases
-	Vapors may cause dizziness or suffocation
-	Runoff from fire control or dilution water may cause pollution
-	

ERG Guide No. 132

### 6. Accidental Release Measures

6.1. Personal Precautions, Protective Equipment and Emergency Procedures: Water spray may reduce vapor; but may not prevent ignition in closed spaces

6.2. Environmental Precautions:

Do not allow spills to enter drains or water courses

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Method and Material for containment and clean up:

Vapor is heavier than air and may flow along surface to distant ignition and source and flashback

CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper is not available or there is no answer, refer to appropriate telephone number listed on the inside back cover.

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away

Stay upwind

Keep our of low areas

Ventilate closed spaces before entering

## <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

7. Handling and Storage

<u>7.1. Precautions For Safe Handling:</u> See Section 2 for further details - [Prevention]

7.2. Conditions for Safe Storage, Including Any Incompatibilities: Handle containers carefully to prevent damage and spillage

Incompatible Materials: Avoid contact with strong oxidizers, strong alkalies, strong mineral acids, phenol and urea.

See section 2 for further details - [Storage]

### 8. Exposure Controls and Personal Protection

8.1. Control Parameters:

Exposure

Cas No.	Ingestion	Source	Value
		OSHA	TWA 0.75 ppmSTEL. 2ppm
		ACHIH	TWA: 0.3 ppm Ceiling: 1 ppmS, A2, 1
000050-00-0	Formaldehyde	NIOSH	Ca TWA 0.016 ppm C 0.1 ppm [15-minute]
		Supplier	No Established Limit
			TWA 200 ppm (260 mg/m3)
		ACHIH	TWA: 200 ppmSTEL: 250 ppm Skin
000067-56-1	1 Methyl Alcohol	NIOSH	TWA 200 ppm (260 mg/mg\3) ST 250 ppm
			(325 mg/m3) [skin]
		Supplier	No Established Limit

# <u>Flush</u>

## ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

8.1. Control Parameters (Con't):

Carcinogen Data

Cas No.	Ingestion	Source	Value	
		OSHA	Select Carcinogen: Yes	
000050-00-0	Formaldehyde	NTP	Known: Yes; Suspected: Yes	
000050-00-0		IARC	Group 1: Yes; Group 2a: No; Group 2b:	
			No: Group 3: No; Group 4: No;	
		OSHA	Select Carcinogen: No	
000067-56-1	Methyl Alcohol	NTP	Known: No; Suspected: No	
000007-50-1		IARC	Group 1: No; Group 2a: No; Group 2b: No:	
			Group 3: No; Group 4: No;	

### 8.2. Exposure Controls:

Respiratory:	Not necessary where area is properly ventilated
Eyes:	Wear safety eyeware, e.g. safety spectacies, googles or visors to protect against the splash of liquids
Skin:	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Wear PVC or rubber gloves
Engineering Controls:	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn
Other Work Practices:	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details – [Prevention]:

9. Physical and Chemical Properties

Appearance:	Clear, slightly viscous, orange-red Liquid
Ordor:	Pungent / Pinching ordor
Order Treshold:	Not Measured
pH:	8.0 – 9.2
Melting Point / Freezing Poing (ºC):	N/A
Initial Boiling Point & Boiling Range (ºC):	65.5 - 100ºC (150 - 212ºF)
Flash Point:	48.3ºC (119ºF)
Evaporation Rate (Ether = 1):	< 1 (n-Butyl acetate = 1)

# <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

#### 9. Physical and Chemical Properties (Con't):

Flammability (solid, gas):	Not Applicable	
Upper/lower flammability or explosive limits:	Lower Explosive Limit: 7%	
	Upper Explosive Limit: 73%	
Vapor Pressure (Pa):	145 – 155 mm Hg	
Vapor Density:	Greater than 1+	
Solubility In Water:	Complete	
Partition coefficient n=octanol/water (Log Kow):	Not Measured	
Auto-ignition Temperature (PC):	Not Measured	
Decomposition temperature:	Not Measured	
Viscosity (cSt):	Not Measured	
VOC %:	97%	

9.2 Other Information:

No other relevant information

10. Stability and Reactivity

#### 10.1. Reactivity:

Hazardous Polymerization will not occur

#### 10.2. Chemical Stability:

Stable under the recommended storage and handling conditions prescribed. At higher temperatures, product may form formic acid and methanol

#### 10.3. Possibility Of Hazardous Reactions:

No data available

#### 10.4. Conditions To Avoid:

Avoid heat and open flame. Exposure to cold may cause precipitation of the polymer; will redissolve upon gentle heating.

#### 10.5. Incompatible Materials:

Avoid contact with trong oxidizers, strong alkalies, strong mineral acids, phenol and urea.

#### 10.6. Hazardous Decomposition Products:

May form formaldehyde gas, carbon oxides, hydrogen, formic acid and various hydrocarbons. Incomplete combustion may also produce irritating smoke and toxic and/or irritating gases or fumes.

## <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

### 11. Toxicological Information

#### ACUTE TOXICITY:

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L 4hr	Inhalation Gas LD50, ppm
Formaldehyde – (50-00-0)	800.00 Rat -	270.00, Rabbit -	0.578, Rat -	No Data	168.00 Rat -
	Category: 4	Category: 3	Category: 2	Available	Category: N/A
Methanol - (67-56-1)	143.00, Human	15,800.00, Rabbit	128.00, Rat -	No Data	64.000.00 Rat -
	– Category: 3	– Category: NA	Category: NA	Available	Category NA

Item	Category	Hazard
Acute Toxicity (mouth)	4	Harmful if swallowed
Acute Toxicity (skin)	3	Toxic in contact with skin
Acute Toxicity (inhalation)	2	Fatal if inhaled
Skin Corrosion / Irritation	1B	Causes severe skin burns and eye damae
Eye Damage / Irritation	1	Causes serious eye damage
Sensitization (respiratory)		Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction
Germ Toxicity	2	Suspected of causing genetic defects
Carcinogenicity	1B	May cause cancer
Reproductive Toxicity		Not applicable
Specific Target Organ Systemic Toxicity (single expsure)	2	May cause damage to organs
Specific Target Organ Systemic Toxicity (repeated exposure)		Not applicable
Aspiration Hazzard		Not applicable

## <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

### 12. Ecological Information

### 12.1. Toxicity:

Very toxic to aquatic life with long lasting effects.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish,	48 hr EC50	ErC50 algae,
	mg/l	crustacea, mg/l	mg/l
Formaldehyde – (50-00-0)	1.41 Oncorhynchus mykiss	5.80 Daphnia pulex	0.788 (96 hr), Ulva pertusa
Methyl Alcohol – (67-56-1)	100.00, Pimephales	10,000.00 Daphina	16.912 (96 hr),
	promelas	magna	Ulva pertusa

### 12.2. Persistence and Degradability:

There is no data available on the preparation itself

### 12.3. Bioaccumulative Potential:

Not Measured

#### 12.4. Mobility In Soil:

No data available

### 12.5. Results of PBT and vPvB assessment:

This product contains no PBT/vPvB chemicals

### 12.6. Other Adverse Effects:

No data available

## <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

### 13. Disposal Considerations

#### 13.1. Waste Treatment Methods:

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollutiion Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

### 14. Transport Information

14.1	UN Number		UN1198			
14.2	UN Proper Shipping Name			Formaldehyde solutions, flammable		
	Transport I			lazard Class(es)		
	DOT (Domestic Surface Transportation)			IMO / IMOG (Ocean Transportation)		
	DOT Proper Shipping	Formaldehyde solutions,		IMDG Proper	Formaldehyde solutions,	
	Name	flammable		Shipping Name	flammable	
14.3	DOT Hazard Class	3		IMDG Hazard Class	3	
	DOT Label	3, 8		Sub Class	Not Applicable	
	UN/NA Number	UN1198		500 61855		
	DOT Packing Group	III		IMDG Packing Group	III	
	CERCLA/DOT RQ	37 Gal. / 309 lbs.				

14.4	Packing Group	III		
14.5	Environmental Hazzards IMDG	Marine Pollutant: Yes	s (Formaldehyde)	
14.6	Special Precautions For Users	Not Applicable		
14.7	Transport In Bulk According To Annex II of MARPOL73/78 and the IBC Code		Not Applic	able

### <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

### 15. Regulatory Information

Regulatory Overview:	The regulatory data in Section 15 is not intended to be all- inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA inventory			
WHMIS Classification:	D2A E			
	Fire:	Yes		
	Sudden Release Of Pressure:	No		
US EPA Tier II Hazards:	Reactive:	No		
	Not Defined:	Yes		
	Delayed (Chronic):	Yes		

- EPCRA 311/312 Chemicals and RQs (lbs): Formaldehyde (100.00) Methanol (5,000.00)
- EPCRA 302 Extremely Hazardous: Formaldehyde
- EPCRA 313 Toxic Chemicals: Formaldehyde Methanol
- Proposition 65 Carcinogens (>0.0%): Formaldehyde
- Proposition 65 Developmental Toxins (>0.0%): (No Product Ingredients Listed)
- Proposition 65 Female Repro Toxins (>0.0%): (No Product Ingredients Listed)
- Proposition 65 Male Repro Toxins (>0.0%): (No Product Ingredients Listed)
- N.J. RTK Substances (>1%): Formaldehyde Methanol
- Penn. RTK Substances (>1%): Formaldehyde Methanol

## <u>Flush</u>

ARLINGTON CHEMICAL CO.

SDS REVISION DATE:

05/28/2015

### 16. Other Information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

#### The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H350 May cause cancer.

H370 Causes damage to organs.

H400 Very toxic to aquatic life.

This is the first revision of this SDS format, changes from previous revision not applicable.

THIS SAFETY DATA SHEET WAS PREPARED USING INFORMATION PROVIDED BY/OBTAINED FROM ARLINGTON CHEMICAL. THE INFORMATION IN THE SAFETY DATA SHEET IS OFFERED FOR YOUR CONSIDERATION AND GUIDANCE WHEN EXPOSED TO THE PRODUCT. ARLINGTON CHEMICAL EXPRESSLY DISCLAIM ALL EXPRESSED OR IMPLIED WARRANTY AND ASSUMES NO RESPONSIBILITIES FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN. THE DATA IN THIS SDS DOES NOT APPLY TO USE WITH ANY OTHER PRODUCT OR IN ANY OTHER PROCESSES AS TO THE ACCURACY OF AND/OR SUFFICIENCY OF SUCH INFORMATION. THIS SAFETY DATA SHEET MAY NOT BE CHANGED OR ALTERED IN ANY WAY WITHOUT THE EXPRESSED KNOWLEDGE AND PERMISSION OF ARLINGTON CHEMICAL.

End of Document